

SCHEDA TECNICA – DATA SHEET - DATENBLATT – FICHE TECHNIQUE

Articolo/Article/Artikel/Article	LINO
Altezza/Width/Breite/Largeur	140 cm
Composizione/Composition/Zusammensetzung/Composition	60%LI 30%CO 10%PL
Peso/Weight/Gewicht/Poids	500 gr/m ² – 700 gr/lm
Prodotta in/Made in/Hergestellt in/Fabriqu�� en	Italia/Italy/Italien/Italie
Tariffa doganale/Custom tariff/Zolltarif/Tarif douani��re	58019010
Resistenza all'abrasione/Abrasion resistance/Scheuerfestigkeit/R��sistance �� l'abrasion (UNI EN ISO 12947-2 / Martindale)	50.000 rubs
Pilling (5.000 cicli)/Pilling (5.000 rubs)Pilling (5.000 scheuertouren)/Pilling (5.000 tours) (UNI EN ISO 12945-2)	5
Solidit�� del colore alla luce/Lightfastness/Lichtechtheit/Solidit�� �� la lumi��re (UNI EN ISO 105 B02 / Xenotest)	5
Solidit�� del colore allo sfregamento/Fastness to rubbing/Reibechtheit / Solidit�� au frottement (UNI EN ISO 105 X12)	secco/dry/trocken/sec 5 umido/wet/nass/humide 4/5
Resistenza alla cucitura/Seam slippage/Nahtschiebewidertand/Glisement �� la couture (UNI EN ISO 13936)	pass
Resistenza alla lacerazione/Tear strength/Weiterreissfestigkeit/Force de d��chirure (UNI EN ISO 13937)	pass
Restringimento/Shrinkage/Schrumpfung/R��tr��cissement (trama/ordito)(warp/weft)(schuss/kette)(trame/cha��ne)	+ / - 3%

NORME MANUTENZIONE/CARE INSTRUCTIONS PFLEGEBEHANDLUNG/INSTRUCTIONS D'ENTRETIEN

